

PV-500EVO2U

Full HD 3" Touch Screen DVR

Now in H.264 Compression!



Feature











- * Touch screen operation & IR remote control
- * 1080P high definition video
- * Frame counter and time stamp functionality
- * Digital & Analog Camera Dual Input
- * 2MP camera compatible
- * Continuous/Motion Detect/Pre-event/Schedule/Pre-Motion Recording Modes
- * User friendly user interface
- * Snap-shot functionality
- * Multiple password protection

Specification



Item Number	PV-500EVO2U
Display	3.0" 960x240 TFT LCD
Video Input	NTSC/ PAL Auto-Detection NTSC/ PAL by UI setting (1.3MP) / (2MP)
Video Recording Mode	Standard/Motion Detection/Schedule/Pre-Event/Pre-Motion
Resolution Mode	320x240 to Max 1920x1080 Real Time
Max. Resolution	Above 720p (1280x960) 1080p(1920x1080) *Available when connected to 2MP camera
Memory Type	SD Card (Supports up to 32GB SDHC)
Frame Rate	1, 5,10,15, 25, 30 fps Adjustable
DC5V to 2.5 Ø phone jack	300mA Max
DC3.3V to mini-HDMI	250mA Max
PC Interface	USB2.0
Image Quality (Bit rate)	Standard 720x576@25fps (PAL) High (5Mbps) / Medium (3.3Mbps) / Low (2.5Mbps) Adjustable
Date & Time Format	YYYY/MM/DD (America) , HH,MM,SS (U.K.)
Frame Counter Stamp	Yes
Picture Format	Baseline JPEG
Power Consumption	Video Playback:480mA Recording:600mA
Battery Life	200min(BU-18) / 140min(CMD-BU13LXU) / 130min(CMD-BU20U) with BA-2200
Dimension	85x54x17mm
Weight	71g

*Specifications are subject to change without prior notice.

Standard Accessories

PI-PV800  IR Controller	S-USB/PV-500  USB Cable
CHG-0520  DC 5V/2A Charger	PT-500  Pouch
S-EP/PV500  Earphone	BA-2200  2200mA Battery
S-PJ2R  AV In Cable	S-1R3R/PV-500  AV Out Cable
PI-WDS10U  Cable Controller	S-MINI USB(WDS)  Controller Cable

Optional Accessories

BCM-DUO1  Dual Battery Charger	BA-4400  4400mA Battery
---	--

Note

The mini USB port is applicable to **CMD-BU13LXU** & **CMD-BU20U** only. PV-500EVO2U does not support CMD-BU13LX & CMD-BU20.